


# AIRNIS SH 32 - 46 - 68



**BEHTAM**  
RAVANKAR



*Compressor*

**PAO Synthetic oils for rotary air compressors.**

## APPLICATIONS

### Rotary air compressors

- Lubrication and cooling of the following types of air compressors:
  - rotary screw compressors (ISO VG 32, 46, 68)
  - reciprocating compressors (ISO VG 100).
- Recommended whenever the discharge temperature exceeds 90°C and/or the discharge pressure exceeds 10 bars.
- Recommended for the lubrication of gears, plain and roller bearings working under severe conditions, where a CKS level is required.

## SPECIFICATIONS

### Meets the requirements of

- ISO 6743 classified DAJ for heavy duty applications.
- ISO DP 6521
- VDL 51506

## ADVANTAGES

### Compressor efficiency optimised

- The properties of **AIRNIS SH**:
  - avoids the carbon build up
  - allows a good oil/air and oil/condensates separation
  - protects the screws against wear and corrosion.

### Operating cost minimised

The use of **AIRNIS SH** allows real cuts in the operating costs of the compressed air production facility by:

- Optimising the compressor efficiency
- Extending the drain intervals. The possible achieved drain intervals can be:
  - from 4000 to 6000 hours for fixed compressors in standard use
  - up to 8000 hours with lubricant analysis monitoring.
- Extending the service life of the separating filter elements.  
The **AIRNIS SH** have an anti-clogging property that ensures the efficiency of the filters during a long period (up to 8000 hours).

TYPICAL CHARACTERISTICS	METHODS	UNITS	AIRNIS SH 32	AIRNIS SH 46	AIRNIS SH 68
Density at 15°C	ASTM D4052	kg/m <sup>3</sup>	835	838	840
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	32	46	68
Viscosity index	ASTM D2270	-	136	139	147
Pour point	ASTM D97	°C	-54	- 49	-45
Flash point (open cup)	ASTM D92	°C	225	230	262

Above characteristics are mean values given as an information.

**BEHTAM CO.**  
AIRNIS SH 32-46-68

[www.btoil.co](http://www.btoil.co)

1/1

